



# AMERICAN BILTRITE

## AB-260

60 DURO NEOPRENE BLEND / COMMERCIAL GRADE / SATIN FINISH / BLACK /  
MODERATE OIL RESISTANT / UNTRIMMED / NO POWDER

| GAUGE                | ITEM NUMBER<br>36" | ITEM NUMBER<br>48" |
|----------------------|--------------------|--------------------|
| SPECIFICATION: BC606 |                    |                    |
| 1/16"                | 266-04-362 (S)     | 266-04-482 (S)     |
| 3/32"                | 266-06-362 (S)     | 266-06-482 (S)     |
| 1/8"                 | 266-08-362 (S)     | 266-08-482 (S)     |
| 3/16"                | 266-12-362 (S)     | 266-12-482 (S)     |
| *1/4"                | 266-16-36S (S)     | 266-16-48S (S)     |

\* Plate Finish (Powdered / Trimmed)  
(S) Normally available from inventory.

### STANDARD DIMENSIONS

| GAUGE | TOLERANCE<br>(+/-) | ROLL LENGTH |      | APPROX. WEIGHT PER ROLL |          | APPROX. SQ. FT. PER ROLL |             |
|-------|--------------------|-------------|------|-------------------------|----------|--------------------------|-------------|
|       |                    | 36"         | 48"  | 36"                     | 48"      | 36"                      | 48"         |
| 1/16" | .016               | 150'        | 150' | 216 LBS.                | 288 LBS. | 450 SQ. FT.              | 600 SQ. FT. |
| 3/32" | .016               | 50'         | 50'  | 110 LBS.                | 146 LBS. | 150 SQ. FT.              | 200 SQ. FT. |
| 1/8"  | .020               | 50'         | 50'  | 146 LBS.                | 194 LBS. | 150 SQ. FT.              | 200 SQ. FT. |
| 3/16" | .031               | 50'         | 50'  | 219 LBS.                | 292 LBS. | 150 SQ. FT.              | 200 SQ. FT. |
| 1/4"  | .031               | 50'         | 50'  | 291 LBS.                | 388 LBS. | 150 SQ. FT.              | 200 SQ. FT. |

Maximum pieces per roll: 2  
Minimum piece length: 10'  
Width tolerance: +1"/-1/2"  
Length tolerance: +/-10%

**Minimum Order:**  
Inventory Item: 1 Roll  
Non-inventory Item: 2,000 lbs.  
Custom Made Item: 3,000 lbs.

### AB-260 PHYSICAL PROPERTIES (Excluding 1/4")

| DESCRIPTION        | TYPICAL VALUE | UNITS               |
|--------------------|---------------|---------------------|
| POLYMER            | CR/SBR/NBR    |                     |
| HARDNESS           | 60            | SHORE "A" DUROMETER |
| TENSILE            | 830           | PSI                 |
| ELONGATION         | 520           | %                   |
| OIL AGING # 1 OIL  | 70 HOURS      | 100 ° C             |
| CHANGED-HARDNESS   | 1             | POINTS              |
| CHANGED-TENSILE    | 3             | %                   |
| CHANGED-ELONGATION | -47           | %                   |
| CHANGED-MASS       | -2            | %                   |
| CHANGED-VOLUME     | 0             | %                   |