



AMERICAN BILTRITE

AB-275

70 DURO NEOPRENE BLEND / INDUSTRIAL GRADE / PLATE FINISH / BLACK / MODERATE OIL RESISTANCE / TRIMMED / WITH PLASTIC LINER (NO POWDER)

GAUGE	ITEM NUMBER 36"	ITEM NUMBER 48"
SPECIFICATION: BC710		
1/16"	275-04-362 (S)	275-04-482 (S)
3/32"	275-06-362	275-06-482
1/8"	275-08-362 (S)	275-08-482 (S)
3/16"	275-12-362 (S)	275-12-482 (S)
1/4"	275-16-362 (S)	275-16-482 (S)
3/8"	275-24-362	275-24-482 (S)
1/2"	275-32-362	275-32-482 (S)
5/8"	275-40-362	275-40-482 (S)
3/4"	275-48-362	275-48-482 (S)
1"	275-64-362	275-64-482 (S)

(S) Normally available from inventory.

Note: Available with powder - minimum quantities apply.

STANDARD DIMENSIONS

GAUGE	TOLERANCE (+/-)	ROLL LENGTH		APPROX. WEIGHT PER ROLL		APPROX. WEIGHT PER ROLL	
		36"	48"	36"	48"	36"	48"
1/16"	.016	150'	125'	212 LBS.	235 LBS.	450 SQ. FT.	500 SQ. FT.
3/32"	.016	75'	65'	158 LBS.	182 LBS.	225 SQ. FT.	260 SQ. FT.
1/8"	.020	75'	65'	212 LBS.	244 LBS.	225 SQ. FT.	260 SQ. FT.
3/16"	.031	60'	45'	254 LBS.	254 LBS.	180 SQ. FT.	180 SQ. FT.
1/4"	.031	45'	35'	252 LBS.	262 LBS.	135 SQ. FT.	140 SQ. FT.
3/8"	.047	45'	35'	379 LBS.	393 LBS.	135 SQ. FT.	140 SQ. FT.
1/2"	.047	45'	35'	506 LBS.	525 LBS.	135 SQ. FT.	140 SQ. FT.
5/8"	.063	30'	30'	422 LBS.	563 LBS.	90 SQ. FT.	120 SQ. FT.
3/4"	.093	30'	30'	507 LBS.	676 LBS.	90 SQ. FT.	120 SQ. FT.
1"	.100	30'	25'	675 LBS.	750 LBS.	90 SQ. FT.	100 SQ. FT.

Maximum pieces per roll: 1/16" to 1/2"-2 pieces, 5/8" to 1" - 1 piece

Minimum piece length: 10'

Width tolerance: +1"/-1/2"

Length tolerance: 1/16" to 1/2" +/-10%, 5/8" to 1" +10%, Min. 10'

Minimum Order:

Inventory Item: 1 Roll

Non-inventory Item: 2,000 lbs.

Custom Made Item: 3,000 lbs.

AB-275 PHYSICAL PROPERTIES

DESCRIPTION	TYPICAL VALUE	UNITS
POLYMER	NBR/SBR/CR	
HARDNESS	70	SHORE "A" DUROMETER
TENSILE	1700	PSI
ELONGATION	400	%
OIL AGING # 1 OIL	70 HOURS	100 ° C
CHANGED-HARDNESS	-3	POINTS
CHANGED-TENSILE	2	%
CHANGED-ELONGATION	-26	%
CHANGED-MASS	-2	%
CHANGED-VOLUME	-1	%

American Biltrite ISO 9001 manufactured product