



# AMERICAN BILTRITE

# AB-465

60 DURO BUTYL / PLATE FINISH / BLACK / TRIMMED / WITH POWDER

GAUGE	ITEM NUMBER 36"	ITEM NUMBER 48"
<b>SPECIFICATION: 3BA610A14C12</b>		
1/16"	360-04-362	360-04-482
1/8"	<b>360-08-362 (S)</b>	<b>360-08-482 (S)</b>
3/16"	360-12-362	360-12-482
1/4"	360-16-362	360-16-482

(S) Normally available from inventory.

## STANDARD DIMENSIONS

GAUGE	TOLERANCE (+/-)	ROLL LENGTH		APPROX. WEIGHT PER ROLL		APPROX. SQ. FT. PER ROLL	
		36"	48"	36"	48"	36"	48"
1/16"	.016	150'	125'	180 LBS.	200 LBS.	450 SQ. FT.	500 SQ. FT.
1/8"	.020	75'	65'	180 LBS.	208 LBS.	225 SQ. FT.	260 SQ. FT.
3/16"	.031	60'	45'	214 LBS.	214 LBS.	180 SQ. FT.	180 SQ. FT.
1/4"	.031	45'	35'	215 LBS.	223 LBS.	135 SQ. FT.	140 SQ. FT.

Maximum pieces per roll: 2  
 Minimum piece length: 10'  
 Width tolerance: +1"/-1/2"  
 Length tolerance: +/-10%

### Minimum Order:

Inventory Item: 1 Roll  
 Non-inventory Item: 2,000 lbs.  
 Custom Made Item: 3,000 lbs.

## AB-465 PHYSICAL PROPERTIES

DESCRIPTION	TYPICAL VALUE	UNITS
POLYMER	BUTYL	
HARDNESS	60	SHORE "A" DUROMETER
TENSILE	1000	PSI
ELONGATION	400	%
HEAT AGING	70 HOURS	100 ° C
CHANGED-HARDNESS	6	POINTS
CHANGED-TENSILE	-7	%
CHANGED-ELONGATION	-25	%

American Biltrite ISO 9001 manufactured product