



# AMERICAN BILTRITE

# AB-616

80 DURO SHEET PACKING / BLACK / PLATE FINISH / TRIMMED / PLASTIC LINER

(NO POWDER)

GAUGE	ITEM NUMBER	ITEM NUMBER
	36"	48"
<b>SPECIFICATION: AA805</b>		
1/16"	<b>111-04-362 (S)</b>	111-04-482
3/32	111-06-362	111-06-482
1/8"	<b>111-08-362 (S)</b>	<b>111-08-482 (S)</b>
3/16"	111-12-362	<b>111-12-482 (S)</b>
1/4"	<b>111-16-362 (S)</b>	<b>111-16-482 (S)</b>

(S) Normally available from inventory.

## STANDARD DIMENSIONS

GAUGE	TOLERANCE (+/-)	ROLL LENGTH		APPROX. WEIGHT PER ROLL		APPROX. SQ. FT. PER ROLL	
		36"	48"	36"	48"	36"	48"
1/16"	.016	140'	105'	202 LBS.	202 LBS.	420 SQ. FT.	420 SQ. FT.
3/32"	.016	95'	70'	205 LBS.	202 LBS.	285 SQ. FT.	280 SQ. FT.
1/8"	.020	70'	55'	202 LBS.	211 LBS.	210 SQ. FT.	220 SQ. FT.
3/16"	.031	45'	35'	194 LBS.	202 LBS.	135 SQ. FT.	140 SQ. FT.
1/4"	.031	35'	25'	202 LBS.	192 LBS.	105 SQ. FT.	100 SQ. FT.

Maximum pieces per roll: 2

Minimum piece length: 10'

Width tolerance: +1"/-1/2"

Length tolerance: +/-10%

### Minimum Order:

Inventory Item: 1 Roll

Non-inventory Item: 2,000 lbs.

Custom Made Item: 3,000 lbs.

## AB-616 PHYSICAL PROPERTIES

DESCRIPTION	TYPICAL VALUE	UNITS
POLYMER	SBR	
HARDNESS	80	SHORE "A" DUROMETER
TENSILE	500	PSI
ELONGATION	300	%

American Biltrite ISO 9001 manufactured product