



AMERICAN BILTRITE

AB-665

65 DURO RED SHEET PACKING / SATIN FINISH / UNTRIMMED / NO POWDER

GAUGE	ITEM NUMBER 36"	ITEM NUMBER 48"
SPECIFICATION: AA607Z1*		*Z1 = 65+/-5
1/16"	313-04-362 (S)	313-04-482 (S)
3/32"	313-06-362	313-06-482
1/8"	313-08-362 (S)	313-08-482 (S)
3/16"	313-12-362	313-12-482 (S)
1/4"	313-16-362	313-16-482 (S)

(S) Normally available from inventory.

STANDARD DIMENSIONS

GAUGE	TOLERANCE (+/-)	ROLL LENGTH		APPROX. WEIGHT PER ROLL		APPROX. SQ. FT. PER ROLL	
		36"	48"	36"	48"	36"	48"
1/16"	.016	63'	47'	100 LBS.	100 LBS.	189 SQ. FT.	188 SQ. FT.
3/32"	.016	42'	32'	100 LBS.	100 LBS.	126 SQ. FT.	128 SQ. FT.
1/8"	.020	31'	24'	100 LBS.	100 LBS.	93 SQ. FT.	96 SQ. FT.
3/16"	.031	21'	16'	100 LBS.	100 LBS.	63 SQ. FT.	64 SQ. FT.
1/4"	.031	15'	12'	100 LBS.	100 LBS.	45 SQ. FT.	48 SQ. FT.

Maximum pieces per roll: 1
 Width tolerance: +1"/-1/2"
 Length tolerance: +/-10%

Minimum Order:
 Inventory Item: 1 Roll
 Non-inventory Item: 2,000 lbs.
 Custom Made Item: 3,000 lbs.

AB-665 PHYSICAL PROPERTIES

DESCRIPTION	TYPICAL VALUE	UNITS
POLYMER	SBR	
HARDNESS	65	SHORE "A" DUROMETER
TENSILE	1000	PSI
ELONGATION	400	%