

Click here for PDF version:



# MATERIAL SAFETY DATA SHEET

## SECTION 1: IDENTIFICATION OF PRODUCT

<b>TRADE NAME:</b>	AB-5271
<b>PRODUCT NUMBER:</b>	NC-908272 A ITEM: 251-04-362 (ref.)
<b>WHMIS CLASS:</b>	NOT CONTROLLED
<b>DESCRIPTION:</b>	NEOPRENE AND SBR RUBBER
<b>PRODUCT USE:</b>	BLACK NEOPRENE SHEET 70 DURO
<b>TRANSPORT:</b>	NOT REGULATED
<b>HMIS CODE:</b>	HEALTH ( ) FIRE ( ) REACTIVITY ( ) SPECIFIC ( ) 0:Minor 1:Light 2:Moderate 3: High 4: Dangerous
<b>SUPPLIER:</b>	American Biltrite ( Canada ) Ltd 200, Bank Street, Sherbrooke, Québec, Canada J1H 4K3 <b>EMERGENCY PHONE NUMBER:</b> (819) 829-3300

## SECTION 2: HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENTS	# CAS	%	T.L.V.	LD50
CRYSTALLINE SILICA QUARTZ	14808-60-7	0.1 - 1.0	0.05 mg / m <sup>3</sup>	7 950 mg/kg (oral-rat)
CARBON BLACK	1333-86-4	10 - 30	3.5 mg / m <sup>3</sup>	>8 000 mg/kg (oral-rat)
N-ISOPROPYL-N'-PHENYL-P-PHENYLENE DIAMINE	101-72-4	1 - 5	N/D	510-950 mg/kg (oral-rat)
NON-ASBESTOS TALC	14807-96-6	0.1 - 1.0	1 mg / m <sup>3</sup>	920 mg/kg (oral-rat)
KAOLIN	1332-58-7	10 - 30	10 mg / m <sup>3</sup>	N/D

### SECTION 3: PHYSICAL PROPERTIES

<b>APPEARANCE AND ODOUR:</b>	Black solid material, rubber odour.
<b>BOILING POINT (°C):</b>	N/A
<b>SPECIFIC GRAVITY (H<sub>2</sub>O=1):</b>	1.49 (approx.)
<b>VAPOUR DENSITY (Air=1):</b>	N/A
<b>MELTING POINT (°C):</b>	N/D
<b>EVAPORATION RATE:</b>	N/A
<b>SOLUBILITY IN WATER (%):</b>	Insoluble.
<b>VOLATILE MATTER (% Vol.):</b>	N/D
<b>VAPOUR PRESSURE (mm of Hg):</b>	N/A
<b>PH:</b>	N/D

### SECTION 4: FIRE AND EXPLOSION HAZARD DATA

<b>FLAMMABLE:</b>	YES ( )      NO (x)
<b>IF YES, IN WHICH CONDITIONS:</b>	
<b>FLASH POINT (°C):</b>	N/D
<b>METHOD:</b>	N/D
<b>AUTO-IGNITION TEMPERATURE (°C):</b>	N/D
<b>FLAMMABLE LIMITS (% VOL.IN AIR):</b>	
<b>LOWER LIMIT:</b> N/D	<b>UPPER LIMIT:</b> N/D
<b>EXTINGUISHING MEDIA:</b>	
WATER SPRAY      (x)	WATER FOG      ( )      CARBON DIOXIDE      ( )
FOAM      (x)	DRY CHEMICAL      (x)
OTHERS      ( )	
<b>SPECIAL FIRE FIGHTING PROCEDURES:</b>	
Wear adequate respiratory protection.	
<b>UNUSUAL FIRE AND EXPLOSION HAZARDS:</b>	
Fire hazard when exposed to flame. Thermal degradation produces flammable hydrocarbon. Molten	

product causes burn when in contact with skin. Dense smoke, explosions hazard with the flammable substance released.

## SECTION 5: REACTIVITY DATA

<b>STABILITY:</b>	UNSTABLE ( )	STABLE	( x )
<b>CONDITIONS TO AVOID:</b>	N/D		
<b>HAZARDOUS POLYMERIZATION:</b>	MAY ( ) OCCUR	WILL NOT OCCUR	( x )