



AMERICAN BILTRITE

TRANSFORMER STOCK

TG50-064

65 DURO SUPREME GRADE NITRILE / BLACK / TRIMMED / WITH POWDER

GAUGE	ITEM NUMBER 36"	ITEM NUMBER 48"
SPECIFICATION:		
1/16"	306-04-362	306-04-482
3/32"	306-06-362	306-06-482
1/8"	306-08-362	306-08-482 (S)
3/16"	306-12-362	306-12-482
1/4"	306-16-362	306-16-482 (S)
3/8"	306-24-362	306-24-482
1/2"	306-32-362	306-32-482

(S) Normally available from inventory.

STANDARD DIMENSIONS

GAUGE	TOLERANCE (+/-)	ROLL LENGTH		APPROX. WEIGHT PER ROLL		APPROX. SQ. FT. PER ROLL	
		36"	48"	36"	48"	36"	48"
1/16"	.016	150'	125'	169 LBS.	188 LBS.	450 SQ. FT.	500 SQ. FT.
3/32"	.016	75'	65'	127 LBS.	146 LBS.	225 SQ. FT.	260 SQ. FT.
1/8"	.020	75'	65'	169 LBS.	195 LBS.	225 SQ. FT.	260 SQ. FT.
3/16"	.031	75'	65'	253 LBS.	293 LBS.	225 SQ. FT.	260 SQ. FT.
1/4"	.031	45'	35'	203 LBS.	210 LBS.	135 SQ. FT.	140 SQ. FT.
3/8"	.047	45'	35'	304 LBS.	315 LBS.	135 SQ. FT.	140 SQ. FT.
1/2"	.047	45'	35'	405 LBS.	420 LBS.	135 SQ. FT.	140 SQ. FT.

Maximum pieces per roll: 2
 Minimum piece length: 10'
 Width tolerance: +1"/-1/2"
 Length tolerance: +/-10%

Minimum Order:
 Inventory Item: 1 Roll
 Non-inventory Item: 2,000 lbs.
 Custom Made Item: 3,000 lbs.

TRANSFORMER STOCK TG50-064

DESCRIPTION	TYPICAL VALUE	UNITS
POLYMER	NBR	
HARDNESS	65	SHORE "A" DUROMETER
TENSILE	2400	PSI
ELONGATION	400	%